

## Features

- Replaces lap splice and hooked rebar
- Reduces congestion
- Eases form placement
- Speeds construction
- A factory-installed cap protects internal threads from being filled with concrete/debris
- Manufactured in the US with domestically produced steel
- Available in sizes #4 (12 mm) & #5 (16 mm) in lengths of 6 in, 7 in and 8 in
- Eliminates protruding dowels
- Eliminates holes in formwork



The LENTON® FORM SAVER ANCHOR mechanical rebar splicing system provides a method of splicing rebar in segmental concrete construction applications that have limited space or rebar congestion. The coupler is friction welded to the headed anchor/shear stud. Typically used in wall applications, the LENTON FORM SAVER ANCHOR easily attaches to the front wall form panel and fits into the wall reinforcement mat more easily than a hooked rebar. When the form is stripped, the protected threaded end of the coupler is exposed on the wall face. Simply remove the protective cap, insert the LENTON® taper threaded dowel bar, and tighten with a standard pipe wrench. This system eliminates hooked bar congestion in walls, protruding dowels and the need to drill holes in expensive formwork. Installation instructions are included with the product.

## After Concrete Pour



The form removal is quick and the protective metal disc is easily removed with a screwdriver.




With the disc removed, the clean internal threads are exposed.

## Install Rebar



Align LENTON taper threaded dowel bar to the LENTON FORM SAVER ANCHOR coupler.



Screw in the LENTON taper threaded dowel bar and tighten with a pipe wrench.

The LENTON® FORM SAVER ANCHOR system is ideal in situations where space is critical, such as:

- Walls
- Stairwells
- Pre-cast wall panels
- Floor slab-to-wall connections
- Beam column connections

The LENTON® FORM SAVER ANCHOR mechanical rebar splicing system conforms with ASTM® A29/A29M and the headed anchor/shear stud is C-1010/C-1020 AWS D1.1 and ASTM-A108 compliant. The bar-to-coupler connection is recognized by or meets the standards of ACI® 318; IBC®, UBC®-97; A.A.S.H.T.O.® Section 8.32.2.3; Concrete Reinforcing Steel Institute; US Army Corp. of Engineers #CW03210; and DOTs including CA, FL, GA, IL, NY, NC and TX.

**Dimension Table**

LENTON FORM SAVER ANCHOR Headed Coupler w/ Plate & Thread Protection

Bar Size			Part Number	Per Piece Weight	Minimum Embedment*
In./Lb.	US Metric	Part Length			
#4	12	5-7/8"	EP4X6	0.8	4-5/8"
#4	12	6-7/8"	EP4X7	0.9	4-5/8"
#4	12	8-1/8"	EP4X8	1.0	4-5/8"
#5	16	6-1/8"	EP5X6	1.0	5-5/8"
#5	16	7-1/8"	EP5X7	1.1	5-5/8"
#5	16	8-1/8"	EP5X8	1.2	5-5/8"

\*Minimum embedment length required to develop 125% of minimum specified yield of ASTM A-615 Grade 60 reinforcing steel in 3000-5000 psi concrete (based on ASME/ACI codes)

WARNING  
 ERICO products shall be installed and used only as indicated in ERICO's product instruction sheets and training materials. Instruction sheets are available at [www.erico.com](http://www.erico.com) and from your ERICO customer service representative. Improper installation, misuse, misapplication or other failure to completely follow ERICO's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death.  
 AASHTO is a registered trademark of American Association of State Highway and Transportation Officials. ACI is a registered trademark of American Concrete Institute.  
 ASME is a registered trademark of American Society of Mechanical Engineers. ASTM is a registered trademark of ASTM International.  
 International Building Code (IBC) is a registered trademark of International Code Council. UBC (Uniform Building Code) is a registered trademark of International Conference of Building Officials.

Copyright ©2009 ERICO International Corporation. All rights reserved.  
 CADDY, CADWELD, CRITEC, ERICO, ERIFLEX, ERITECH, and LENTON are registered trademarks of ERICO International Corporation.