


## HARDWARE ROD COUPLING 25

### Steel Rod Coupling

- Size Range: 1/4" thru 7/8" rod sizes
- Surface Finish: Electro-zinc Plated
- Intermediate accessory designed to join two lengths of similar UNC threaded rod

Part Number	RS	L	Max. Rec. Load (lbs)
0250025EG	1/4"	7/8"	240
0250037EG	3/8"	1-3/4"	610
0250050EG	1/2"	1-3/4"	1130
0250062EG	5/8"	2-1/8"	1810
0250075EG	3/4"	2-1/4"	2710
0250087EG	7/8"	2-1/2"	3770




## HARDWARE ROD COUPLING 25S

### Short Steel Rod Coupling

- Size Range: 3/8" and 1/2" rod sizes
- Surface Finish: Electro-zinc Plated
- Intermediate accessory designed to join two lengths of similar UNC threaded rod

Part Number	RS	L	Max. Rec. Load (lbs)
025S0037EG	3/8"	1-1/8"	N/A
025S0050EG	1/2"	1-1/4"	N/A



# HARDWARE ROD COUPLING 25R

## Reducing Steel Rod Coupling

- Size Range: 3/8", 1/2" and 5/8" rod sizes
- Surface Finish: Electro-zinc plated
- Intermediate accessory designed to join dissimilar sizes of UNC rod

**NOTE:** Never use smaller rod sizes than the minimum rod sizes noted in MSS-SP-69



Part Number	RS	RS1	L	Max. Pipe Size	Max. Rec. Load (lbs)
025R3725EG	3/8"	1/4"	1"	3/8"	240
025R5037EG	1/2"	3/8"	1-1/4"	2"	610
025R6250EG	5/8"	1/2"	1-1/4"	3-1/2"	1130

