





CABS Busbar Support Kit – CABS2-10TN-600 (549270)



- For all busbar types
- Improve bending resistance by interlocking or stacking two profiles
- Quick and easy to install
- Halogen free insulators
- RoHS compliant



Part Number	CABS2-10TN-600
Article Number	549270
Material	Aluminum Glass Fibre Reinforced Polyamide Steel
Finish	Electrogalvanized
Typical Application Current Rating	400 – 4,500 A
Max Working Voltage, IEC (Ui)	1,000 VAC 1,500 VDC
Working Temperature	-40 to 266 °F
Complies With	IEC® 60439.1 IEC® 61439.1 IEC® 60695-2-11 (Glow Wire Test 960 °C)
Flammability Rating	UL® 94V-0
Busbars per Phase	1 – 2
Busbar Width	1.18" – 4.72"
Busbar Thickness	0.39"
Depth [D]	1.54"
Width [W]	21.65"
A	19.69"
B	2.95" – 4.92"
C	20.67"
Unit Weight	1.79 lb
Certifications	Bureau Veritas 41941 BV CE, ERIFLEX CABS IEC 61439-1 Busbar Supports RoHS

Part Number	CABS2-10TN-600
Standard Packaging Quantity	1 pc
UPC	78285687571
EAN-13	3479775492704

IEC is a registered trademark of the International Electrotechnical Commission. UL, UR, cUL, cUR, cULus and cURus are registered certification marks of UL LLC.

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.erico.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

© 2021 nVent All rights reserved

nVent, nVent CADDY, nVent ERICO, nVent ERIFLEX and nVent LENTON are owned by nVent or its global affiliates.

All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without prior notice.